

**LED EMERGENCY BULKHEADS** 

Low energy alternative to standard fluorescent emergency bulkheads

- Polycarbonate construction Internal or external use 20mm gland entries as standard
- Hinged gear tray & push fit terminal block; allows for quicker and easier installation and maintenance
- Minimum 3 hour functionality in emergency mode High output LEDs with bright white light
- Semi recessed fixing option available: BULKFRAME allows a more discreet installation option
- Dedicated self adhesive legend pack included with a combination of symbols: allows multiple exit path designation options
- Additional legend sets available: ISOLGDSET (ISO 7010 format) / LGDSET (signs directive format) which can be used as additional legend sets or as individual stickers for walls and doors
- Viewing distance 20m

## **MAINTAINED VERSIONS:**

- · Facility for remote switching and non-maintained mode
- 235 lm when connected to mains, 150 lm when connected to battery


## **BULKFRAME:**


- Pressed steel construction Spring retaining clips
- · Semi recessed fixing: allows a more discreet installation option
- Hole cut out size: 350mm x 117mm

## SEEMLED3M:

- Automatic testing in accordance with EN 62034
- Fittings / Frame = M.O.M: 1 / O.P.Q: 12
- Legends = M.O.M: 12 / O.P.Q: 12







## PERFECT FOR OFFICE, COMMERCIAL **AND INDUSTRIAL APPLICATIONS**







Code

SEEMLED3M

**EML3MISO** 

EMLED3M

**EML3NMISO** 



355mm 70mm					
Version	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating
Self Test Maintained With ISO 7010 Legend Set	7W	6000K	235 lm (mains) 150 lm (battery)	30,000 hrs	IP65
Maintained With ISO 7010 Legend Set					
Maintained With Signs Directive Legend Set					
Non Maintained With ISO 7010 Legend Set					

150 lm

2W

**EMLED3NM** Non Maintained With Signs Directive Legend Set BULKFRAME White Bulkhead Frame **ISOLGDSET** ISO 7010 Legend Set

**LGDSET** Signs Directive Legend Set \*Subject to terms & conditions

Hinged gear tray