

Sensor-switched outdoor light

L 585 S

black

EAN 4007841 005535

STEINEL[®]
Intelligent technology



max.60w



infrared sensor
180°



max. 10 m



IP44



70° vertical



2 - 2000 lux



8 sec - 35 min



ideal 2 m



energy saving



manufacturer's
warranty
steinel.de/garantie

Function description

Individualist all round. Outdoor SensorLight L 585 S, ideal for building fronts and entrances, 180° angle of coverage, reach up to 10 m, selectable time and twilight threshold, sensor tilts through 70° for exact adjustment of the detection zone.

Technical specifications

Dimensions (L x W x H)	307 x 215 x 228 mm
Mains power supply	230 – 240 V / 50 Hz
Mounting height max.	3,00 m
Sensor Technology	passive infrared
Output	60 W
Interconnection	No
With lamp	No
Lamp	All-purpose lamp
Base	E27
With motion detector	Yes
Detection angle	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	No
Mechanical scalability	No

Reach, radial	r = 3 m (14 m ²)
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	8 s – 35 Min.
Impact resistance	IK03
IP-rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Plastic
Cover material	Glass transparent
Manufacturer's Warranty	3 years
Settings via	Potentiometers
Version	black
PU1, EAN	4007841005535

Sensor-switched outdoor light


L 585 S

black

EAN 4007841 005535

STEINEL[®]
Intelligent technology

Detection Zone



Mögliche Montagehöhe: 1,80 m – 3,00 m

Orange: radial

Schwarz: tangential

Dimension Drawing

