
1 22

Stainless steel EAN 4007841 009816







max.60w



















max. 60 W E27

frared sensor 180°

max. 10 m

IP44

2 - 2000 lu

8 sec - 35 m

shock proof IK

deal 2 m

energy savi

#### **Function description**

The inviting light solution! Designer sensor-switched outdoor light L 22 with attractive stainless steel trim, ideal for building entrances and building fronts,  $180^{\circ}$  angle of coverage, reach up to 10 m, selectable time and twilight threshold, sensor tilts through  $90^{\circ}$ .

# **Technical specifications**

Dimensions (L x W x H)	286 x 162 x 85 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Mounting height max.	3,00 m
Sensor Technology	passive infrared
Output	60 W
Interconnection	No
With lamp	No
Lamp	All-purpose lamp
Base	E27
With motion detector	Yes
Detection angle	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	No
Mechanical scalability	No


Reach, radial	$r = 3 \text{ m } (14 \text{ m}^2)$
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	8 s – 35 Min.
Impact resistance	IK07
IP-rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Stainless steel
Cover material	Plastic, opal
Manufacturer's Warranty	3 years
Settings via	Potentiometers
Version	Stainless steel
PU1, EAN	4007841009816

## Sensor-switched outdoor light

Stainless steel EAN 4007841 009816



#### **Detection Zone**



Mögliche Montagehöhe: 1,80 m – 3,00 m Orange: radial Schwarz: tangential

## **Dimension Drawing**

