


Sensor-switched outdoor light

L 600 CAM

EAN 4007841 052997



LED

14,3 w



3000K warm-white



infrared sensor
180°



max. radius 10 m



2,4 GHz WiFi



Intercom system



Camera



inclusive



IP44

30 years (Ø 4,5h /
day)

781 lm, 54 lm/W

Function description

Smart. Save. Intelligent. L 600 CAM is a sensor-switched camera and intercom system in one product. With integrated micro SD memory card and camera to get razor-sharp images onto the smartphone or tablet (Wi-Fi and app-based). Enclosure in aluminium and high-quality opal glass. 180° infrared motion sensor with 10 m reach. Warm-white light: 3000 K and 781 lm at 14,3 W.

Technical specifications

Dimensions (L x W x H)	131 x 78 x 305 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Mounting height max.	2,00 m
Sensor Technology	passive infrared
Output	14,3 W
Interconnection	No
Luminous flux	781 lm
Efficiency	54 lm/W
Colour temperature	3000 K
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Base	without
LED cooling system	Passive Thermo Control
With motion detector	Yes
Detection angle	180 °
Angle of aperture	90 °
Sneak-by guard	No

Capability of masking out individual segments	No
Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	r = 2 m (6 m ²)
Photo-cell controller	Yes
Twilight setting	10 – 10000 lx
Time setting	60 s – 15 Min.
Basic light level function	Yes
Soft light start	Yes
Impact resistance	IK03
IP-rating	IP44
Protection class	I
Ambient temperature	-10 – 40 °C
Housing material	Aluminium
Cover material	Glass opal
Manufacturer's Warranty	3 years
Settings via	Wi-Fi
With remote control	Yes
PU1, EAN	4007841052997

<https://www.steinell.de>


Sensor-switched outdoor light

L 600 CAM

EAN 4007841 052997




Detection Zone




Mögliche Montagehöhe: 1,80 m – 2,00 m
Orange: radial
Schwarz: tangential

Dimension Drawing



Master circuit diagram



Master/slave interconnection circuit diagram

