



General Information

| | |
|--------------------|--------------------------------------------------------|
| Dimensions | 1500mm (L) x 96mm (W) x 83mm (D) |
| Materials | Base: Polycarbonate Frosted Diffuser: Polycarbonate |
| Base Finish | Light Grey |
| Product Weight | 2.00Kg |
| Dimmable | No |
| Ingress Protection | IP65 |
| IK Rating | IK08 |
| Mounting | Ceiling, Wall or Suspended |
| Warranty | 5 Years |

Supply & Power

| | |
|---------------------------|------------------------------------------|
| Input Voltage & Frequency | 230V~ 50Hz |
| Electrical Safety | Class I |
| LED Wattage | 55W |
| Circuit Wattage | 55W |
| Input Current | 275mA |
| Inrush Current | 8A (432ms) |
| Power Factor | >0.9 |
| Ambient Temperature (Ta) | -20°C - +40°C |
| Critical Temperature | +90°C |
| Terminations | 5 Pole Push Fit Terminal Block |
| Cable Input Component | 20mm IP68 Nylon Gland Supplied |
| Fixing Components | Surface and Suspension Brackets Supplied |

Luminaire Output

| | |
|-----------------------|------------------------------------------|
| Colour Temperature | 4000K |
| CRI | >80 |
| Typical Luminous Flux | 6600lm |
| Efficacy | 120lm/W |
| Beam Angle | 105° |
| LED Lifetime (L70) | 50,000 Hours |
| Fixing Components | Surface and Suspension Brackets Supplied |

