

DISPLAY & LED STRIPS

SURFACE MOUNT 70W & 150W HQI PROJECTOR



Code	RD70S	RD150S
Total Power (W):	70	150
Light output (lm):	3500	7500
Tilt/turn (Deg):	90/360	90/360
Lamp excluded – use:	LHQI70N	LHQI150N
Cap Type:	RX7S	RX7S
Length (mm):	220	220
Width (mm):	170	170
Height (mm):	100	100
Box Qty:	6	6
IP:	20	20
Guarantee (Yrs):	2	2
Weight (Kg):	3.5	3.9



These powerful metal halide projectors really give a tremendous punch of light and are ideal for accent illumination of many display type applications or for mounting at height for directional general illumination. With a high colour rendering index these fittings bring out the sleek lines and vivid colours enticing customers to look, touch and feel the displayed items. These fittings find applications in:

- Bars & Clubs
- Churches
- Temporary exhibition stands
- Retail shops
- Stage lighting
- Exhibition centres
- Architectural features
- Showrooms

FEATURES	BENEFITS
• Powder coated finish	• Attractive aesthetically pleasing • Tough and durable finish • Easy to clean
• Die cast aluminium body	• Strong and not easily damaged • Provides excellent heat dissipation for long lamp and gear life
• Stirrup type mounting bracket	• Suitable for wall or ceiling mounting • Provides tilt & turn facility to aim light in a specific direction • Does not require mounting above the area to be lit
• Tempered glass	• Ensures safety if lamp breaks on failure
• Complete with HPF control gear	• Integral power factor correction reduces the real power consumption
• High lumen output	• Ideal for any application requiring high light levels
• Energy efficient	• Complies with Building Regulations Part L2 for display lighting
• High CRI	• Reproduces true vivid colour to the eye for optimum rendering
• Uses optional RMTA-01 mechanical & RTA-xx electrical adapter	• Provides compatibility with Robus single circuit track

PLEASE NOTE – INFORMATION CONTAINED IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE