

**Product Code:** CCA066

**Description:** Twin Non-Isolated Coaxial Outlet



Representative Image

## General Information

<b>Dimensions</b>	86mm (W) x 86mm (H) x 9.5mm (D)
<b>Plate Design &amp; Finish</b>	Rounded Profile Polar White
<b>Materials</b>	Front Plate: Urea Earth Plate: Mild Steel Terminals: Brass
<b>Plate Fixing Centres</b>	60.3mm
<b>Isolated</b>	Non-isolated (Direct connection to aerial where 2 way signal is required)
<b>Shielded</b>	No
<b>Ingress Protection</b>	IP20
<b>Back Box Depth</b>	16mm Minimum
<b>Operational Temperature</b>	-5°C to +40°C
<b>Warranty</b>	10 Years

## Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.  
 All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases.  
 All products have been independently tested and achieved a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.