

Technical Specification



Product Code: CMA652

Description: 13A Double Pole Switched Fused Connection Unit With Neon

FUSE				
General Infor	mation			
Plate Dimensio		86 (W) x 86 (H) x 9.5 (D)		
Plate Fixing Centres - Horizontal (mm)		60.3		
Style		Rounded Profile		
	Finish	Polar White		
Materia		Front Plate, Rocker Switch & Fuse Drawer:		
		Urea	Rear Housing: Urea	
		Neon Lens: Polycarbonate	Terminals: Brass	
		Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on	
		Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Ste	eel
Anti Microbial Certified		Yes		50
Rated Voltage (V~) (Ue) Resistive Load Rating (A)		250	Frequency (Hz)	50
	- · ·	13 12A (PS 1260)		
Fuse Fitted Rating & Type		13A (BS 1362) Screw		
Termination Type Terminal Size (mm)			al Torque Value (Nm)	2
Terminal Capacity - Solid (mm²)		3 x 2.5 or 2 x 4		2
	Switched	Yes		
Double Pole Switch		Yes		
Twin Earth Terminals		Yes		
Neon Indicator		Yes	Indicator Colour	Orange
Product Marking		Fused		orange
Minimum Back Box Depth (mm)		25		
Ingress Protection		IP20		
Operational Temperature (°C)		-5 to +40		
	y (Years)			
Standards	BS 1363 BS 1362	-4		
Additional Information	Ensure t diagram Bare ear All white propertie propertie	hat the mains supply is isolated before comme with the relevant product. th cables must always be covered with approp moulded accessories are manufactured using to antimicrobial additives that inhibit the grow as against enveloped and non-enveloped viruse with have been independently tested with 90 9	riate sleeving and wired Urea Formaldehyde, w vth of infectious diseas es.	d to the earth termina hich has similar inhe es as well as anti-vir

All products have been independently tested with 99.9% of enveloped viruses and 92% of nonenveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

> UK CA

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

Page 1 of 1 (30/06/22) Errors & Omissions excluded. Specification is subject to change without notice.