



Main

Range	TeSys
Device short name	VZ
Product or component type	Additional pole
Performance level	High performance
Poles description	1P
Contacts type and composition	1 NO
Product compatibility	V4
Network type	AC DC
Network frequency	50/60 Hz
Mounting location	Left Right

Complementary

[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	80 A
[Ithe] conventional enclosed thermal current	63 A
Mechanical durability	30000 cycles
Electrical durability	30000 cycles DC-1...5 100000 cycles AC-21
Suitability for isolation	Yes
Connections - terminals	Power circuit : screw clamp terminals cable 25 mm ² - cable stiffness: solid - Power circuit : screw clamp terminals cable 16 mm ² - cable stiffness: flexible - with cable end cable end
Tightening torque	Power circuit : 4 N.m - on screw clamp terminals
Height	83 mm
Width	20 mm
Depth	46 mm
Product weight	0.1 kg

Environment

Standards	IEC 60947-3
Product certifications	CSA GL UL
Protective treatment	TC
IP degree of protection	IP20 conforming to IEC 60529
Mechanical robustness	Vibrations 10...150 Hz 1 gn IEC 60068-2-6 Shocks 30 Gn IEC 60068-2-27
Ambient air temperature for operation	-20...50 °C
Fire resistance	960 °C conforming to IEC 60695-2-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.