



Main

Range of product	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for modular device
Accessories included with enclosure	1 terminal block support 2 terminal block 32 holes 3 marking kits 3 wiring straps

Complementary

Enclosure mounting	Surface
Number of 18 mm modules per row	12
Total number of 18 mm modules	36
Number of horizontal rows	3
Provided equipment	Terminal block 32 holes for 2 Terminal block support for 1 Wiring strap for 3 Marking kit for 3
Type of front cover	Reversible Transparent
Type of rail	DIN
Number of pre-cutouts PG ISO	17
Number of terminal blocks	2 with 32 outgoers
Distribution block outgoers	32 x 16 mm ² 32 x 10 mm ²
Locking options description	Optional keylock
Enclosure material	Plastic
Width	340 mm
Height	610 mm
Depth	160 mm
Colour	Enclosure :light grey (RAL 7035) Door :transparent green

Environment

Standards	EN 50102 EN 50262 IEC 60439-3 IEC 60529 IEC 60695-2-1 IEC 670
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

Contractual warranty

Period	18 months
--------	-----------