



Main

| | |
|-------------------------------------|--|
| Enclosure type | Weatherproof enclosure |
| Range of product | Kaedra |
| Device short name | Kaedra for modular devices |
| Accessories included with enclosure | 1 terminal block support 2 marking kits 2 terminal block 22 holes 2 wiring straps |

Complementary

| | |
|---------------------------------|---|
| Enclosure mounting | Surface |
| Type of front cover | Reversible Transparent |
| Number of horizontal rows | 2 |
| Number of 18 mm modules per row | 12 |
| Total number of 18 mm modules | 24 |
| Type of rail | DIN |
| Number of pre-cutouts PG ISO | 17 |
| Number of terminal blocks | 2 22 |
| Distribution block outgoers | 22 x 10 mm ² 22 x 16 mm ² |
| Locking options description | Optional keylock |
| Enclosure material | Plastic |
| Width | 340 mm |
| Height | 460 mm |
| Depth | 160 mm |
| Colour | Light grey RAL 7035 enclosure Transparent green door |

Environment

| | |
|---------------------------------------|--|
| Standards | EN 50102 EN 50262 IEC 60439-3 IEC 60529 IEC 60695-2-1 IEC 670 |
| Fire resistance | 650 °C IEC 60695-2-1 |
| IP degree of protection | IP65 IEC 60529 |
| IK degree of protection | IK09 EN 50102 |
| Electrical shock protection class | Class II |
| Ambient air temperature for operation | -25...60 °C |
| RoHS EUR conformity date | 0648 |
| RoHS EUR status | Compliant |