

### Main

Commercial Status	Commercialised
Range of product	TeSys
Device short name	LE1D
Product or component type	Enclosed DOL starter
Motor starter type	Non reversing
Motor power kW	7.5 kW at 380/400 V AC 50/60 Hz 9 kW at 440 V AC 50/60 Hz 9 kW at 415 V AC 50/60 Hz 4 kW at 220/230 V AC 50/60 Hz 10 kW at 660/690 V AC 50/60 Hz 10 kW at 500 V AC 50/60 Hz
Utilisation category	AC-3
[Uc] control circuit voltage	400 V AC 50/60 Hz
[Ith] conventional free air thermal current	18 A
Control type	1 red stop/reset button O red 1 green start button I green
Enclosure material	Polycarbonate

### Complementary

Device composition	Contacteur
Protection type	Thermal protection via thermal overload relay to be ordered separately
Cable entry	2 x 16 mm PG at bottom 2 x 20 mm ISO at top 2 x 20 mm PG at bottom 2 x 21 mm PG at bottom 2 x 25 mm ISO at top 2 x 25 mm PG at bottom
Width	101 mm
Height	201 mm
Depth	153.5 mm
Product weight	1.015 kg

### Environment

IP degree of protection	IP657 conforming to IEC 60529
Standards	EN 60947 IEC 60439-1 IEC 60947-4-1 VDE 0660-102
Ambient air temperature for operation	-5...40 °C

### RoHS compliance

RoHS EUR status	Compliant
RoHS EUR conformity date(Y Y W W)	0817

### Contractual warranty

Period	18 months
--------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.