



## Main

Range	TeSys
Product name	TeSys VARIO
Device short name	VCF
Product or component type	Emergency stop switch disconnecter
Performance level	High performance
Poles description	3P
Contacts type and composition	3 NO
Network type	AC DC
Control type	Rotary handle
Rotary handle mounting style	Direct
Handle colour	Red
Handle front plate colour	Yellow
Rotary handle padlocking	1 to 3 padlocks 4...8 mm

## Complementary

Marking	0 - 1
Mounting support	Door forhandle
Fixing mode	By 4 screws for handle
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	40 A
[Ithe] conventional enclosed thermal current	32 A
[Ie] rated operational current	29 A (AC-23) at 400 V
Rated operational power in W	11 kW 690 V (AC-3) 15 kW 690 V (AC-23A) 11 kW 400...415 V (AC-3) 15 kW 500 V (AC-3) 18.5 kW 500 V (AC-23A) 5.5 kW 230...240 V (AC-3) 7.5 kW 230...240 V (AC-23A) 15 kW 400...415 V (AC-23A)
Intermittent duty class	30
Making capacity	400 A 400 V (AC-21A) 400 A 400 V (AC-22A) 400 A 400 V (AC-23A)
[Icm] rated short-circuit making capacity	1 kA 400 V at Ipeak
[Icw] rated short-time withstand current	480 A 400 V during 1 s
Rated conditional short-circuit current	10 kA 400 V - associated fuse 50 A aM 10 kA 400 V - associated fuse 50 A gG
Breaking capacity	320 A 400 V AC-21A 320 A 400 V AC-22A 320 A 400 V AC-23A
Device composition	Handle Switch
Mechanical durability	100000 cycles
Electrical durability	30000 cycles DC-1...5 100000 cycles AC-21
Suitability for isolation	Yes
Connections - terminals	Power circuit : screw clamp terminals cable 10 mm <sup>2</sup> - cable stiffness: solid -

Power circuit : screw clamp terminals cable 6 mm<sup>2</sup> - cable stiffness: flexible - with cable end cable end

Tightening torque	Power circuit : 2.1 N.m - on screw clamp terminals
Base dimension	60 x 60 mm
Height	74 mm
Width	60 mm
Product weight	0.25 kg
Compatibility code	Main switch disconnecter

## Environment

Standards	IEC 60947-3
Product certifications	CCC CSA GL UL
Protective treatment	TC
IP degree of protection	IP65 IP20 conforming to IEC 60529
Mechanical robustness	Vibrations 10...150 Hz 1 gn IEC 60068-2-6 Shocks 11 ms 30 Gn IEC 60068-2-27
Ambient air temperature for operation	-20...50 °C
Fire resistance	960 °C conforming to IEC 60695-2-1

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0733 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations